

SP-WMO20W/40W/50W



DESCRIPTION

SP-WMO20W/40W/50W is a high-performance 20W/40W/50W wall-mount speaker designed for superior audio delivery in both indoor and outdoor environments. With its rugged IP66-rated waterproof construction, this speaker ensures reliable performance in challenging weather conditions, making it ideal for public spaces, educational institutions, transportation hubs, industrial areas, and commercial venues.

FEATURES

- Powerful Sound Output:** 20W/40W/50W of high-quality sound with clear audio reproduction for music and announcements.
- Weather-Resistant Design:** The IP66 waterproof rating protects against dust, heavy rain, and harsh weather conditions.
- Durable Construction:** High-impact ABS housing and corrosion-resistant grille for extended outdoor durability.
- Wide Sound Coverage:** Optimized driver design ensures consistent sound projection over a broad area.
- Flexible Mounting Options:** An adjustable wall mounting bracket allows precise installation and directional audio coverage.
- Versatile Applications:** Suitable for both background music and voice broadcasts in demanding environments.
- Stylish and Compact Design:** A sleek, modern appearance that blends seamlessly into any architectural style.
- Durable Construction:** Built with high-grade materials for long-lasting performance and resistance to environmental damage.



SPECIFICATIONS

Model	SP-WMO20W	SP-WMO40W	SP-WMO50W
Tweeter	1" silk soft dome	1" silk soft dome	1" silk soft dome
Woofer	5" Graphite cone, rubber surround	6.5" Graphite cone, rubber surround	8" Graphite cone, rubber surround
Frequency Range +/-	100Hz-20,000Hz	60Hz -20,000Hz	80Hz-20,000Hz
Power Handling RMS	20W	40W	50W
Max. SPL	98dB±3dB	102dB±3dB	104dB±3dB
Sensitivity	85dB±3dB	86±3dB	87±3dB
Impedance	8 ohms	8 ohms	8 ohms
Termination	Pluggable terminal blocks	Pluggable terminal blocks	Pluggable terminal blocks
Dimensions H*W*D	258mm*168mm*163mm	285mm*200mm*195mm	381mm*250mm*250mm
Housing Material	ABS	ABS	ABS
Certificate	IP66 waterproof	IP66 waterproof	IP66 waterproof
Power Adjustment 70V	1.25W-2.5W-5W-10W	2.5W-5W-10W-20W	3.12W-6.25W-12.5W-25W
Power Adjustment 100V	2.5W-5W-10W-20W	5W-10W-20W-40W	6.25W-12.5W-25W-50W
Power Adjustment 8Ω	20W	40W	50W
Coverage	≥110°	116	120

Cannex Technology Inc.

台灣日旭科技

No.182, Sec. 2, Yuanlu Rd., Sihu Town 514, Changhua County, Taiwan Tel:- +886-4-8613883, FAX;-
+886-6-8828209, Email:- sales@amplimic.com.tw
Home Page : <http://www.amplimic.com.tw>

CANNEX reserves the right to modify product specifications without prior notice