Ultra slim Retractable Monitor

Ultra slim Retractable Monitor

DESCRIPTION

The **Amplimic Ultra Slim Retractable Monitor** is an integrated, premium aluminum solution that combines a high-quality A+ grade IPS panel with a smooth, motorized lift mechanism. Designed for professional environments, it features dual signal inputs and an automatic 15° tilt for optimal viewing ergonomics.

FEATURES

- **Premium Display:** High quality IPS panel (A+ grade) with wide viewing angles.
- **Integrated Design:** Ultra-slim integrated design combining the monitor and lift mechanism.
- **Adjustable Tilt:** Automatic 15° backward tilt after lifting; manual adjustment up to 30°
- **Dual Signal Inputs:** Supports HDMI + VGA (optional 2×HDMI), selectable via panel or control system.
- **Integrated Controls:** Top plate includes Up/Stop/Down keys, USB (with dust cover), HDMI/VGA selection.
- **PC Power Management:** Features a separate PC power ON/OFF button with a dedicated indicator.
- **Smooth Motion:** Stable lifting via dual guide shafts, rack transmission, and AC geared motor drive.
- **Aluminum Construction**: Lightweight and premium aluminum structure.
- **Power Distribution:** Supports daisy-chain power pass-through (hand-in-hand connection).
- **Sizes:** Available in 4 screen sizes - 15.6", 17.3" and 21.5" and 23.8"

SPECIFICATIONS

Model	ULM-1560	ULM-1730	ULM-2150	ULM-2380
Screen Size	15.6”	17.3"	21.5"	23.8"
Format	16:9	16:9	16:9	16:9
Display Color	16.7m(10bit)	16.7m(10bit)	16.7m(10bit)	16.7m(10bit)
Resolution	1920 × 1080	1920 × 1080	1920 × 1080	1920 × 1080
Viewing Angle (Typ.)	89/89/89/89	89/89/89/89	89/89/89/89	89/89/89/89
Response Time	50ms	50ms	50ms	50ms
Contrast Ratio	800:1	1000:1	1000:1	1000:1
Brightness	350 cd/㎡	350 cd/㎡	300 cd/㎡	300 cd/㎡
Panel Interface	2×HDMI, USB, RS485	2×HDMI, USB, RS485	2×HDMI, USB, RS485	2×HDMI, USB, RS485
Power Input	AC 220V, 50–60Hz	AC 220V, 50–60Hz	AC 220V, 50–60Hz	AC 220V, 50–60Hz
Power Consumption	< 25W	< 25W	< 25W	< 25W
Lift Time	17sec	17sec	17sec	17sec
Auto Tilt Angle	15°	15°	15°	15°
Manual Tilt Angle	up to 30°	up to 30°	up to 30°	up to 30°
Display Thickness	8 mm	8 mm	12 mm	18 mm
Overall Dimension (W×D×H)	430*70*700mm	476*70*700 mm	582*70*700 mm	630*80*700mm.
Power Supply	220V	220V	220V	220V

No.182, Sec. 2, Yuanlu Rd., Sihu Town 514, Changhua County, Taiwan Tel:- +886-4-8613883, FAX;- +886-6-8828209, Email:- sales@amplimic.com.tw
Home Page : http://www.amplimic.com.tw

AMPLIMIC reserves the right to modify product specifications without prior notice